

Product Description:

PACHIN Turbo is Interior Emulsion Putty based on acrylic copolymer emulsion.

Features :

- * Easy to apply
- * No sagging on vertical substrate
- * Easy to sand
- * Very good filling ability

Fields of application :

- PACHIN Turbo is an excellent and economic water base filler used to eliminate and level surface imperfections for new and old cement or plaster for interior and exterior surfaces.

Technical Data:

<i>Colors</i>	<i>White</i>
<i>Solids by volume</i>	<i>52 % ± 2</i>
<i>Solids by weight</i>	<i>73 % ± 2</i>
<i>Specific gravity</i>	<i>1.80 ± 0.03</i>

Theoretical Spreading Rate:

1 – 2 m²/kg (At dry film thickness 250 microns).

DRYING TIME: (At 25°c & 60% R.H)

<i>Surface dry</i>	<i>Through dry</i>	<i>Recoating time</i>	
		<i>Min.</i>	<i>Max.</i>
<i>1/2 hr</i>	<i>-</i>	<i>Min.2 hrs</i>	<i>No limitation</i>



TURBO

PACHIN P

COLOR

APPLICATION DATA:

- Application tools : Putty knife.
- Thinner : Tap water
- Cleaning Thinner : Tap water

SURFACE PREPARATION:

As a general rule. All new surfaces or already painted surfaces should be free from dirt, grease, waxes etc.

IDEAL PAINT SYSTEMS:

- New cement and plaster surface should be primed by PACHIN sealer or clear varnish 3860 to insure excellent adhesion of the filler PACHIN Turbo and the subsequent layers (undercoat – finish).
- PACHIN Turbo is applied using putty knife in two cross layers with a time interval of 2 hours between the two coats sanding should be done the next day.

VALIDITY:

2 years from the production date if stored in original sealed container and at the rights conditions away from direct sunlight.

HANDLING : Handle with care and stir well before use.

PACK SIZE : 15 kg. (In Addition to other Packages for Projects)

