
PAVEMENT PAINT 11132

Description:	It is a semi matt pavement paint based on modified alkyd resin. This item complies with E.S.NO 794.
Advantages:	<ul style="list-style-type: none"> • Very high resistance to direct sun rays. • Very high durability. • Fast drying. • Flow and easy to apply. • Very high resistance to solvents, dusts, water and rains. • Very high resistance to abrasion.
Fields of application:	<ul style="list-style-type: none"> • Used as pavement paint in roads.
Color:	According to PACHIN color shades.
Finish:	Semi Matt.
Specific gravity:	1.45 gm / cm ³
Solid by volume:	55 %.
Theoretical spreading rate:	7 - 8 m ² / kg (at D.F.T 50 micron).
Wet film thickness:	220 microns.
dry film thickness:	120 microns.
Drying time:	<ul style="list-style-type: none"> • Surface: 60 min. (at 25°C & 60% R.H.). • Complete: 2 hrs. (at 25°C & 60% R.H.).
Time to recoat:	<ul style="list-style-type: none"> • Min.: 2 hrs. (at 25°C & 60% R.H.). • Max.: no limit.
Shelf life:	6 months in its closed original cans at good stores in ideal conditions.
Thinner:	No. 11500 (PACHIN thinner).
Method of application:	<ul style="list-style-type: none"> • By brush and roller: Volume of thinner: 0 - 5 %
Surface preparation:	<ul style="list-style-type: none"> • The surface should be dry and clean from dirties, oils and greases.