
TRAFFIC PAINT 11024

Description:	It is a traffic matt paint based on modified alkyd resin. This product complies with E.S. No. 794.
Advantages:	<ul style="list-style-type: none"> • Fast drying. • High resistance to direct sun ray. • Very high resistance to solvents, rusts, water and rains. • Very high resistance to abrasion.
Fields of application:	<ul style="list-style-type: none"> • Used as a road marking paint.
Color:	White, yellow and black.
Finish:	Semi Matt.
Specific gravity:	1.5 ± 0.1 gm / cm ³
Solid by volume:	55 ± 2 %.
Theoretical spreading rate:	3 - 4 m ² / kg (at D.F.T 120 micron).
Wet film thickness:	220 microns.
dry film thickness:	120 microns.
Drying time:	<ul style="list-style-type: none"> • Surface: 30 min. (at 25°C & 60% R.H.). • Complete: 1 hr. (at 25°C & 60% R.H.).
Time to recoat:	<ul style="list-style-type: none"> • Min.: 2 hrs (at 25°C & 60% R.H.). • Max.: no limit.
Shelf life:	6 months in its closed original cans at good stores in ideal conditions.
Thinner:	No. 10152 (PACHIN thinner).
Method of application:	<ul style="list-style-type: none"> • By brush (for small areas) : Volume of thinner: 0 - 5 % • By spraying equipment for long lines (high way) Volume of thinner: 0 - 5 %