
FAST DRY ALKYD ENAMEL NO. 11094

Description:	It is a synthetic air drying enamel based on modified alkyd resin gives a glossy film.
Advantages:	<ul style="list-style-type: none"> • Fast drying. • Flow and easy to apply. • Very high protective to the painted surfaces. • Give a good gloss, color retention. • Good weather resistance. • Abrasion resistance. • Very high adhesion.
Fields of application:	<ul style="list-style-type: none"> • Used for interior and exterior surfaces. • It is suitable for concrete, wood and steel.
Color	As PACHIN shades.
Finish	Gloss.
Specific gravity:	1.1 ± 0.05 gm / cm ³
Solid by weight:	53 % (approx.).
Theoretical spreading rate:	8.5 m ² / kg (at D.F.T 50 micron).
Wet film thickness:	100 microns.
dry film thickness:	45 microns.
Drying time:	<ul style="list-style-type: none"> • Surface: 30 min. (at 25°C & 60% R.H.). • Complete: 24 hrs. (at 25°C & 60% R.H.).
Time to recoat:	<ul style="list-style-type: none"> • Min.: 12 hrs. (at 25°C & 60% R.H.). • Max.: no limit.
Shelf life:	12 months in its closed original cans at good stores in ideal conditions.
Thinner:	No. 10152 (PACHIN thinner).
Method of application:	<ul style="list-style-type: none"> • By airless spray: Volume of thinner: 0 - 5 % Nozzle orifice: 0.02" - 0.025" Nozzle pressure: 160 bar • By air spray: Volume of thinner: 0 - 10 % Nozzle orifice: 1.8 - 2 mm Nozzle pressure: 3 bar • By brush and roller (for small areas) Volume of thinner: 0 - 5 %
Surface preparation:	<ul style="list-style-type: none"> • The surface should be dry and clean from dirties, oils and greases, it should be applied on primed metal surfaces.