

---

**FAST DRY ANTI - CORROSIVE PRIMER NO. 11093**


---

<b>Description:</b>	It is a fast dry synthetic primer based on special types of pigments.
<b>Advantages:</b>	<ul style="list-style-type: none"> <li>• Fast drying.</li> <li>• Long time Anti - corrosive primer.</li> <li>• Flow and easy to use.</li> </ul>
<b>Fields of application:</b>	<ul style="list-style-type: none"> <li>• Used as anti - corrosive primer for steel structures, pipes, tanks.</li> </ul>
<b>Color</b>	White, grey and yellow.
<b>Finish</b>	Flat.
<b>Specific gravity:</b>	1.35 ± 0.05 gm/cm <sup>3</sup>
<b>Solid by weight:</b>	66 % (approx.).
<b>Theoretical spreading rate:</b>	7 - 9 m <sup>2</sup> / kg (at D.F.T 35 micron).
<b>Wet film thickness:</b>	100 microns.
<b>dry film thickness:</b>	46 microns.
<b>Drying time:</b>	<ul style="list-style-type: none"> <li>• Surface: 10 - 20 min. (at 25°C &amp; 60% R.H.).</li> <li>• Complete: 1 - 2 hrs. (at 25°C &amp; 60% R.H.).</li> </ul>
<b>Time to recoat:</b>	<ul style="list-style-type: none"> <li>• Min.: 4 hrs. (at 25°C &amp; 60% R.H.).</li> <li>• Max.: no limit.</li> </ul>
<b>Shelf life:</b>	12 months in its closed original cans at good stores in ideal conditions.
<b>Thinner:</b>	No. 10152 (PACHIN thinner).
<b>Method of application:</b>	<ul style="list-style-type: none"> <li>• By airless spray.</li> <li>• By air spray.</li> <li>• By brush and roller.</li> </ul>
<b>Surface preparation:</b>	<ul style="list-style-type: none"> <li>• Steel should be free from oil, greases and dust.</li> <li>• Steel mechanically cleaned to remove surface rust.</li> </ul>