
ALUMINITE PAINT NO. 11404

Description:	It is an aluminum finish coat with heat resisting properties up to 180°C.
Advantages:	<ul style="list-style-type: none"> • high heat resistance paint. • Very high adhesion. • Give a semi gloss surface. • Flow and easy to use.
Fields of application:	<ul style="list-style-type: none"> • Used on steel for interior and exterior uses exposed to high temperatures up to 180 °C. • Used on tanks, pipes ...etc. • Could be used on exhaust pipes.
Color	Aluminum.
Finish	Semi gloss.
Specific gravity:	1.00 ± 0.05 gm / cm ³
Solid by volume:	45 % (approx.).
Theoretical spreading rate:	9 m ² / kg (at D.F.T 50 micron).
Wet film thickness:	100 microns.
dry film thickness:	45 microns.
Drying time:	<ul style="list-style-type: none"> • Surface: 4 - 6 hrs. (at 25°C & 60% R.H.). • Complete: 7 days (at 25°C & 60% R.H.).
Shelf life:	12 months in its closed original cans at good stores in ideal conditions.
Thinner:	No. 11500 (PACHIN thinner).
Method of application:	<ul style="list-style-type: none"> • By air spray: Nozzle orifice: 2 - 3 mm Nozzle pressure: 3 - 4 bar • By brush or roller: (for small areas) Volume of thinner: 0 - 5 %
Surface preparation:	<ul style="list-style-type: none"> • The surface should be dry and clean from dirties, oils and greases, it should be applied on primed metal surfaces.