
ACRYLIC TOP COAT NO. 11452

Description:	It is a high quality paint based on acrylic modified resin.
Advantages:	<ul style="list-style-type: none"> • Give excellent durability. • Give excellent light fastness. • Excellent mechanical properties. • Flow and easy to apply. • Very high adhesion. • Has good gloss. • High color retention. • Excellent weather resistance.
Fields of application:	<ul style="list-style-type: none"> • Apply on steel, wood, fiber and plastic surfaces which is well primed. • Could be applied as a finish coat for all automotive types. • Could be applied as finish coat on steel surfaces in marines and petroleum tanks.
Color	As PACHIN shades.
Finish	High gloss.
Specific gravity:	1.1 ± 0.1 gm / cm ³
Solid by volume:	65 ± 3 %.
Theoretical spreading rate:	10 m ² / kg (at D.F.T 50 micron).
Wet film thickness:	100 microns.
dry film thickness:	65 microns.
Drying time:	<ul style="list-style-type: none"> • Surface: 30 min. (at 25°C & 60% R.H.). • Complete: 24 hrs. (at 25°C & 60% R.H.).
Time to recoat:	<ul style="list-style-type: none"> • Min.: 2 - 3 hrs (at 25°C & 60% R.H.). • Max.: no limit.
Shelf life:	12 months in its closed original cans at good stores in ideal conditions.
Thinner:	No. 10773 (PACHIN thinner).
Method of application:	<ul style="list-style-type: none"> • By airless spray. • By air spray. • By brush and roller (for small areas).
Surface preparation:	<ul style="list-style-type: none"> • The surface should be dry and clean from dirties, oils and greases, it should be applied on primed metal surfaces.